



DATE

PROJECT

COMMENTS

PRODUCT FEATURES

FIXTURE HOUSING


Width: 3.0" Height: 3.5"

ONE-PIECE EXTRUDED ALUMINUM HOUSING

Housing ensures straighter rows and consistent lens retention

120/277VAC 0-10 VOLT DIMMING TO 1% STANDARD

UP TO 136.7 LUMENS PER WATT AT 90 CRI



ORDERING GUIDE EX: 3C - 20 - HD - 30 - UNV - WH - C90

SERIES	LENGTH	OUTPUT		CCT	VOLTAGE	FINISH
3C	XX FT	VHD	1250 LM/FT	LD	500 LM/FT	30 3000K UNV 120-277V WH White
	2' Increments EX: 20' = 20	HD	1000 LM/FT	VLD	250 LM/FT	35 3500K 347' 347V BLK Black
		MD	750 LM/FT	CD	Custom	40 4000K

ORDERING NOTES


- EM NOT AVAILABLE WITH 347V.
- EM NOT AVAILABLE WITH 2' FIXTURES.
- FOR INDIVIDUAL FIXTURES, SENSOR LOCATED AT POWER FEED END. FOR RUNS, A SENSOR IS INSTALLED INTO EACH FIXTURE IN RUN, EX. 2 SENSORS ARE INSTALLED IN A 16 FT RUN (1 SENSOR IN EACH 8 FT FIXTURE)

OPTIONS

CRI	INTEGRATED CONTROLS ³	OPTICAL	FOR INDIVIDUALS	FOR LINEAR RUNS ^{5, 6}
C90				EM
C90 90 CRI	DOS Daylight Occupancy Sensor DALI DRIVER STANDARD	BLANK = LAMBERTIAN	EM ² Emergency Battery CEC LISTED	EMERGENCY BATTERY PACK QUANTITY PER RUN* POSITION IN RUN*
		WW ⁴ Wall Wash, Direct	EC Emergency Circuit	EC
				EMERGENCY CIRCUIT QUANTITY PER RUN* POSITION IN RUN*

EMERGENCY OPTION NOTES

- INTEGRATED CONTROLS NOT AVAILABLE WITH WALL WASH.
- EM AND EC QUANTITY IS NOT TO EXCEED NUMBER OF DISCRETE FIXTURE SECTIONS IN A ROW.
- EM AND EC POSITION REFERS TO WHICH FIXTURE IN THE RUN THAT WILL BE POWERED BY THE EM/EC CIRCUIT. POSITION OPTIONS: S=STARTER, J=JOINER, E=ENDER
EX: 3C-20-HD-35-UNV-WH-EM2SJ




PHOTOMETRICS

3C-04-HD-35-UNV-XX-C90

Total Lumens: 3,999
Ratio: 0% Up & 100% Down
Wattage: 31.8
Efficacy: 126.0 LM/W
Fixture Length: Four Feet

Zonal Lumen Summary

Zone	Lumens	% Fixt
0 - 30	1136.0	28.4
0 - 40	1828.8	45.7
0 - 60	3145.9	78.7
0 - 90	3997.3	99.9
90 - 180	2.09	0.1
0 - 180	3999.4	100.0




3C-04-HD-35-UNV-XX-C90-WW

Total Lumens: 4,057
Ratio: 0% Up & 100% Down
Wattage: 32.0
Efficacy: 127.0 LM/W
Fixture Length: Four Feet

Zonal Lumen Summary

Zone	Lumens	% Fixt
0 - 30	1302.7	32.1
0 - 40	2069.4	51.0
0 - 60	3396.3	83.7
0 - 90	4056.4	100.0
90 - 180	0.23	0.0
0 - 180	4056.6	100.0



ENERGY CONSUMPTION

WATTS PER LINEAR FOOT

DIRECT (LAMBERTIAN) LIGHT AT 90 CRI

	VHD	HD	MD	LD	VLD
W/FT	10.4	8.0	5.9	3.9	2.0
LM/FT	1255	999	755	499	268
LM/W	120.7	124.9	128.0	127.9	136.7

DIRECT (WALL WASH) LIGHT AT 90 CRI

	VHD	HD	MD	LD	VLD
W/FT	10.4	8.0	5.9	3.9	2.0
LM/FT	1274	1014	766	506	272
LM/W	122.5	126.7	129.9	129.9	138.8

OPERATION

Light Engine:

The 3C is available in 3000K, 3500K and 4000K CCT all within a 3-Step MacAdam Ellipse and has a standard CRI of 90+.

Optics:

The back-lit extruded acrylic lens ensures high efficiency light output, in a minimal form factor for a clean, evenly illuminated surface with minimal glare.

Optional Wall Wash:

Asymmetric extruded aluminum reflector with recessed extruded acrylic lens to achieve a superior wall uniformity while minimizing glare.

Electrical:

Class 2 programmable (factory pre-set) premium power supply, 120-277VAC input. Power factor >0.9. THD <15%. Integral Surge Protection to 2KV.

Dimming:

The 2C comes standard with 0-10V dimming down to 1%.

Emergency Battery Pack:

Emergency Battery Pack has been engineered to exceed UL minimum safety standards. Standard battery is CEC Listed. For most fixtures, the entire direct portion of the fixture will be illuminated by the EM Battery Pack. For 8' VHD, 10' HD and VHD, and 12' MD, HD, and VHD, only the first portion of the fixture will be illuminated by the EM battery pack. "Quantity per Run" refers to the number of fixtures in the run that will be supplied with an emergency battery pack. "Position in Run" refers to which fixture in the run that will contain the battery. Position options are Starter (S), Joiner (J), or Ender (E). For example, a 24' run needing two emergency battery packs, one in the starter and one in the joiner, would be ordered as EM2SJ. When a joiner is selected, battery packs are always supplied in 8' fixtures before 6' fixtures in that run.

Emergency Circuit:

Emergency Circuit fixtures are engineered so that the entire fixture is wired to the emergency circuit. "Quantity per Run" refers to the number of fixtures in the run that are wired to the emergency circuit. "Position in Run" refers to which fixture in the run that will be powered by the Emergency Circuit. Position options are Starter (S), Joiner (J), or Ender (E). For example, a 24' run with needing two emergency sections, one in the starter and one in the joiner, would be ordered as EC2SJ. When a joiner is selected, Emergency Circuits are always supplied in 8' fixtures before 6' fixtures in that run.

GENERAL

Warranty:

Ten (10) Year limited warranty from date of shipment.

Lumen Maintenance:

Rated for 85% initial lumen output at 90,000 Hours of operation, operated at 25°C ambient temperature; per TM-21 Guidelines published by the Illuminating Engineering Society (IES).

Certifications:

All Luminaires are UL/cUL Listed to UL 1598 Standards and approved for Indoor use in Dry/Damp Locations.

MECHANICAL

Housing Construction:

Extruded Aluminum 6063-T5 alloy outer housing with die-formed steel internal components for strength, alignment, and mounting attachment. Our high-quality die-cast end caps are engineered to conceal all fasteners and to retain the sealing gaskets on the inside of the fixture while completing the clean and minimalistic look of this luminaire.

Alignment/Assembly:

The alignment system employs a four-point alignment and attachment method, designed to create straighter rows and minimize seams between sections (field assembled). Four alignment pins ensure the outer extruded aluminum rails are aligned, while a draw-screw secures housing-to-housing attachment. Additional alignment biscuits double as the light shields.

Lengths:

The 3C is available in a minimum 2-foot (nominal) length with additional 2-foot increments available (± 0.030 "). Longer fixture rows are available and will be configured per ALL factory specifications; typical rows are configured with 4-foot, 6-foot and 8-foot fixtures. Max run length on one power feed is 72'. Continuous runs over 72' will require 2 power feeds.

Mounting Method/Hardware:

The 3C is available for mounting upon any ceiling type, additional mounting hardware available by others.

Exterior Finish:

The 3C is available in White and Black polyester powder coat finish to ensure durability.

Integrated Controls:

The 3C is available with optional integrated controls. Sensors are conveniently designed to mount in aperture. For individual fixtures, the sensor is located at the power feed end. For runs, each Starter, Joiner and Ender fixture will be supplied with a discrete sensor that will control that specific fixture within the run.

Shipping:

2-Week lead time for orders up to 1000 Linear Feet.


4-Week lead time for orders with a Black finish.

Lead time for orders greater than 1,000' will be determined at time of order.

Manufactured in the USA:


All ALL Luminaires and Components (with the exception of our LED boards and drivers) are proudly manufactured and assembled in the USA.

MOUNTING DETAILS




FIXTURE ROW LAYOUT: SINGLE UNIT 2' - 4' - 6' - 8' - 10' - 12'


2' FIXTURE




4' FIXTURE




6' FIXTURE




8' FIXTURE



10' FIXTURE




12' FIXTURE




FIXTURE ROW LAYOUT: TWO UNITS 14' - 16'

14' FIXTURE




16' FIXTURE




FIXTURE ROW LAYOUT: THREE UNITS 18' - 20' - 22' - 24'


18' FIXTURE




20' FIXTURE



22' FIXTURE



24' FIXTURE



FIXTURE ROW COMPONENTS

RUN LENGTH (FT)	FIXTURE LENGTHS									JOINER KITS	END-CAPS	END-CAP TO END-CAP
	STARTER	JOINER										
	1	2	3	4	5	6	7	8	9			
14	6'	-	-	-	-	-	-	-	8'	1	2	168.5"
16	8'	-	-	-	-	-	-	-	8'	1	2	192.5"
18	4'	6'	-	-	-	-	-	-	8'	2	2	216.5"
20	4'	8'	-	-	-	-	-	-	8'	2	2	240.5"
22	6'	8'	-	-	-	-	-	-	8'	2	2	264.5"
24	8'	8'	-	-	-	-	-	-	8'	2	2	288.5"
26	4'	6'	8'	-	-	-	-	-	8'	3	2	312.5"
28	4'	8'	8'	-	-	-	-	-	8'	3	2	336.5"
30	6'	8'	8'	-	-	-	-	-	8'	3	2	360.5"
32	8'	8'	8'	-	-	-	-	-	8'	3	2	384.5"
34	4'	6'	8'	8'	-	-	-	-	8'	4	2	408.5"
36	4'	8'	8'	8'	-	-	-	-	8'	4	2	432.5"
38	6'	8'	8'	8'	-	-	-	-	8'	4	2	456.5"
40	8'	8'	8'	8'	-	-	-	-	8'	4	2	480.5"
42	4'	6'	8'	8'	8'	-	-	-	8'	5	2	504.5"
44	4'	8'	8'	8'	8'	-	-	-	8'	5	2	528.5"
46	6'	8'	8'	8'	8'	-	-	-	8'	5	2	552.5"
48	8'	8'	8'	8'	8'	-	-	-	8'	5	2	576.5"
50	4'	6'	8'	8'	8'	8'	-	-	8'	6	2	600.5"
52	4'	8'	8'	8'	8'	8'	-	-	8'	6	2	624.5"
54	6'	8'	8'	8'	8'	8'	-	-	8'	6	2	648.5"
56	8'	8'	8'	8'	8'	8'	-	-	8'	6	2	672.5"
58	4'	6'	8'	8'	8'	8'	8'	-	8'	7	2	696.5"
60	4'	8'	8'	8'	8'	8'	8'	-	8'	7	2	720.5"
62	6'	8'	8'	8'	8'	8'	8'	-	8'	7	2	744.5"
64	8'	8'	8'	8'	8'	8'	8'	-	8'	7	2	768.5"
66	4'	6'	8'	8'	8'	8'	8'	8'	8'	8	2	792.5"
68	4'	8'	8'	8'	8'	8'	8'	8'	8'	8	2	816.5"
70	6'	8'	8'	8'	8'	8'	8'	8'	8'	8	2	840.5"
72	8'	8'	8'	8'	8'	8'	8'	8'	8'	8	2	864.5"

	FIXTURE LENGTH	FEED DIMENSIONS
4'	48.0"	21.0"
6'	72.0"	36.0"
8'	96.0"	48.0"

